

# HARDMOUNT WASHERS

THW 11 · 14 · 18

---



## STANDARD FEATURES & BENEFITS

- Rigid mounted, medium spin
- High G-factor: 200 G
- Large door opening for easy loading and unloading
- Detergent dispenser in 4 compartments
- Standard equipped for automatic soap dosing
- Drum and tub made of robust and durable high quality stainless steel AISI 304
- Highly flexible and freely programmable control with advanced 4,3" touch control for easy operation and perfect management of your laundry business
- 8 dosing signals
- Intelligent weighing system for optimal loading
- Low water consumption
- USB connection in the front for quick data transfer
- Electronic control of imbalance with frequency control
- Loading aid feature: water and rotation control

## OPTIONS

- Opposite door opening
- Coin or token version
- Stainless steel AISI 304 outer casing
- Stainless steel AISI 304 front panel
- Double drain valve
- 6 extra dosing signals
- Floor anchoring base

TOLON

# HARDMOUNT WASHERS

## THW 11 · 14 · 18

MODEL	UNIT	THW 11	THW 14	TWE 18			
<b>DRUM</b>							
Load capacity 1:9 / 1:10	Kg	11/10	14/13	20/18			
Volume	l	100	130	180			
Diameter	mm	620	620	700			
Depth	mm	330	430	470			
<b>GENERAL DETAILS</b>							
Washing speed/ Spinning speed	r.p.m.	50/762	50/762	50/714			
G-force	-	200	200	200			
Maximum force transmitted	KN	2,0 ±3	2,31 ±4	2,63 ±5			
Frequency-dynamic force	Hz	8,93	8,93	8,42			
Noise level	dB	<70	<70	<70			
Coin laundry version	-	Yes	Yes	Yes			
Double drain	-	No	Opt	Opt			
Weighing system / Tilting system	-	No/No	No/No	No/No			
<b>DOOR</b>							
Height center door/ Height door	mm	570/310	570/310	655/348			
Diameter	mm	373	373	460			
<b>POWER</b>							
Motor	kW	1,1	1,1	2,2			
Electric heating power	kW	6	9	12			
Total electric power (electric model)	kW	6,3	9,5	12,75			
Total electric power (hw, steammodel)	kW	1,1	1,1	2,2			
<b>CONNECTIONS</b>							
		<b>ELECTRICAL</b>	<b>STEAM / HOT WATER</b>	<b>ELECTRICAL</b>	<b>STEAM / HOT WATER</b>	<b>ELECTRICAL</b>	<b>STEAM / HOT WATER</b>
Tension 230V- I + N + T	N° x mm <sup>2</sup> / A	2x4+T / 32A	2x1,5+T / 6A	2x10+T / 50A	2x1,5+T / 6A	2x16+T / 63A	2x1,5+T / 10A
Tension 230V- III + T	N° x mm <sup>2</sup> / A	3x2,5+T / 20A	-	3x4+T / 32A	-	3x6+T / 40A	-
Tension 400V- III + N + T	N° x mm <sup>2</sup> / A	4x1,5+T / 16A	-	4x1,5+T / 16A	-	4x2,5+T / 20A	-
Steam inlet (Steam model)	inch	1/2"		1/2"		1/2"	
Maximum steam consumption (Steam model)	Kg/h	7		8,5		12	
Water inlet	inch	3/4"		3/4"		3/4"	
Water main pressure	Kgs/cm <sup>2</sup>	2-4		2-4		2-4	
Maximum water consumption*	Lit/h	59,8		79,4		118,70	
Drain	inch	3"		3"		3"	
Drainage capacity	Lit/min	200		200		200	
<b>DIMENSIONS / PACKING DIMENSIONS</b>							
Net Width / Gross Width	mm	719/800		719/800		788/840	
Net Depth / Gross Depth	mm	684/850		830/990		840/1.010	
Net Height / Gross Height	mm	1.158/1.350		1.158/1.350		1.307/1.500	
Net weight / Gross weight	kg	217/225		239/247		281/301	
Volume	m <sup>3</sup>	1,07		1,07		1,27	

\* N°20 Program, 75% load

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

[www.tolon.com](http://www.tolon.com)

**TOLON**