

# TUMBLE DRYERS

## TRDS 11 · 16



### STANDARD FEATURES & BENEFITS

- Stacked tumble dryer in skinplate, cream color
- Big loading door (opening of 180°)
- Direct drive through a gearbox, no pulley
- Digital control and electronic control. Easy and intuitive to use, the electronic control offers a complete control of the process
- Reverse drum: all models offer the reverse turning of the drum
- Drum in galvanised steel
- New filter drawer with wide surface and improved airflow, filter grid is standard 0,6 mm in stacked dryers
- Cool down: anti-wrinkle at the end of cycle
- Models available in electric or gas heating
- Self-service: to connect to a central payment system or with 2 coiners as it can be ordered with 2 coin kits + boxes, a token kit can be ordered with the token box

### OPTIONS

- Moisture control
- Double doorglass
- Stainless steel drum with mixed axial-radial flow and punched drum holes
- Stainless steel body
- Stainless steel front panel
- Opposite door opening
- Lint filter with dia. 0,3 or 1,2 mm mesh
- Wooden box packing
- Special voltages
- Mechanical meter for coin / token
- Electronic coin kit

TOLON

# TUMBLE DRYERS

## TRDS 11· 16

MODEL	UNIT	TRDS 11	TRDS 16
Capacity 1/18	kg	24	36
Capacity 1/20	kg	21	33
Hourly output *	kg/h	36	53
Evaporation capacity *	l/h	16,5	18,6
<b>DRUM</b>			
Ø Drum	mm	750	750
Ø Door	mm	574	574
Door center height	mm	547 / 1.522	547 / 1.522
Load hole bottom height	mm	260 / 1.235	260 / 1.235
Drum depth	mm	475	746
Drum volume	l	210	330
<b>POWER</b>			
Drum motor	kW	0,37 x 2	0,37 x 2
Fan motor	kW	0,25 x 2	0,25 x 2
Electric heating	kW	12 x 2	12 x 2
Total electric power	kW	25,34	25,34
Gas heating	kW	12 x 2	12 x 2
<b>CONNECTIONS</b>		<b>ELECTRICAL - GAS</b>	<b>ELECTRICAL - GAS</b>
Tension 230V - I + N + T	No x mm <sup>2</sup> / A	- 3 x 1,5 / 20A	- 3 x 1,5 / 20A
Tension 230V - III + T	No x mm <sup>2</sup> / A	4 x 25 / 80A 3 x 1,5 / 20A	4 x 25 / 80A 3 x 1,5 / 20A
Tension 400V - III + N + T	No x mm <sup>2</sup> / A	5 x 10 / 40A 3 x 1,5 / 20A	5 x 10 / 40A 3 x 1,5 / 20A
<b>DIMENSIONS / PACKING DIMENSIONS</b>			
Net Width / Gross Width	mm	785 / 865	785 / 865
Net Depth / Gross Depth	mm	972 / 1.055	1.242 / 1.325
Net Height / Gross Height	mm	1.980 / 2.126	1.980 / 2.126
Net Weight / Gross Weight	kg	260 / 268	290 / 303
<b>OTHERS</b>			
Max airflow	m <sup>3</sup> /h	1000	1000
Ø Fume exhaust	mm	200	200
Sound level	dB	64	64

\* It may vary depending on the type of heating, filter cleanliness or extraction type.